









The Offset ceiling light is characterised by its linear design and easy surface installation. The Low-Glare High Efficiency linear model allows for highly energy efficient installations and minimal glare. The structure is aluminium with powerful Led light strips, a versatile fitting offering static and Tunable White lighting options to customise spaces according to individual project requirements. A stylish and sustainable solution for a warm and light filled ambience.

Model Sheet

Finish	 23 Warm White NCS S 0502-Y50R
	 90 Black NCS S 8500N
	 24 Beige M1 NCS S 2005-Y50R
LED temperature color	2700 K / 3000 K / 3500 K / Tunable White
Dimming	CASAMBI / DALI / PUSH / PROTOPIXEL
Installation type	Surface

Materials	Body: Aluminum Body: PE- Polyethylene Frame: PC- Polycarbonate
Light source	1 x LED STRIP 27,4W 650mA 
LED	CRI>90 3348 lm 122.63 2700 K / 3000 K / 3500 K / Tunable White
Driver	Constant Current 650 220~240 V V 50~60 Hz HZ
Application	  Dimmable 
	 50-60Hz 
	Ceiling Lamps
Packaging	Box Gross weigth Net weigth

Lighting effect

Linear High Efficiency - Low Glare
High energy efficiency and low glare levels
UGR<19 for linear light applications

Photometric Data

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty