









Respecting our natural circadian rhythms, the low-glare, high-efficiency Line model eliminates unwanted glare, providing soft, general lighting for a comfortable interior or a subtle transition between different settings. Frameless model.

Model Sheet

Finish	 04 Black NCS S 8500N
	 23 Warm White NCS S 0502-Y50R
LED temperature color	2700 K / 3000 K / 3500 K / Tunable White
Dimming	On/Off / NO DRIVER / PUSH DALI / CASAMBI
Installation type	Built-in
Materials	Body: ABS Diffuser: PE- Polyethylene Frame: Aluminum
Light source	1 x undefined 
LED	CRI>90 897 lm 123,9 2700 K / 3000 K / 3500 K / Tunable White
Driver	Constant Current 650 220~240 V V 50~60 Hz HZ
Remarks	Trimless frame included. / Possibility of early shipping of the Trimless frame.     
Application	Ceiling Lamps
Packaging	1 Box 0.15 m x 0.3 m x 0.075 m Gross weight 0.01 Net weight 0.01 Vol. 0.0033

Lighting effect

Linear High Efficiency - Low Glare

High energy efficiency and low glare levels
UGR<19 for linear light applications

Photometric Data

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com