


Bind solo



6600

VIBIA

Bind Solo provides an indirect down lighting offering a perfect integration within its surrounding architecture by being totally recessed.

Model Sheet



Finish	 04 Black NCS S 8500N
	 24 Beige M1 test ral
LED temperature color	2700 K / 3000 K / 3500 K
Dimming	PUSH DALI / NO DRIVER / CASAMBI / On/Off
Installation type	Remote driver Built-in Micro

Materials	Body: Aluminum Optics: PMMA- Methacrylate
-----------	--

Light source	1 x LED 4.3W 250 mA
--------------	---------------------



LED	CRI>90 451 lm 104,9 2700 K / 3000 K / 3500 K
-----	---

Driver	Constant Current 250 220~240 V V 50~60 Hz HZ
--------	---



Application	Ceiling Lamps
-------------	---------------

Packaging	1 Box 0.15 m x 0.15 m x 0.075 m Gross weight 0.63 Net weight 0.15 Vol. 0.0016
-----------	---

Lighting effect

Accent

Narrow: Angles less than 20°. Suitable for generating high contrasts or projections at far distances. Medium: Angles between 20° and 40°. Suitable for generating medium contrasts or projections at medium distances. Wide: Angles greater than 40°. Suitable for generating moderate contrasts or projections at near distances



Photometric Data

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com