Guise



2292

Design By Diez Office

Ceiling light. The larger diameter glass cylinder is held vertically, concentrating the light within a lower corona of light. The pattern of striations etched into the borosilicate glass irradiates a general light with a moiré effect of visual interference crowned by a fine halo. The light source is hidden by the upper black profile.

Model Sheet







Finish 18 Graphite
ADAPTA RF 9913 WX

LED temperature color

Dimming

3000 K

1-10V PUSH

Optional DALI or Casambi Min. quantity, upcharge and extra

lead time apply [EN]

Instalation type Surface Canopy

Materials Ceiling rose: Steel Body: Aluminum

Light source 1 x LED STRIP 24V 12W

G

LED CRI>90 1325 lm 118

3000 K

Driver CV - Constant Voltage [object

Object] 110~240 V 50/60 HZ

Remarks Sensor on the LED base

Ei-volt 50-60Hz

Application Ceiling Lamps

Packaging 1 Box

0.385 m x 0.385 m x 0.3 m Gross weigth 4.2 Net weigth 2.2 Vol. 0.0444

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

 Efficiency
 26.02 lm/W

 Coordinate System
 C=0.00 G=0

 Total Flux
 398.74 lm

 Maximum Value
 329.76 cd

Other Applications





All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty