


Model Sheet




Finish	18 Graphite ADAPTA RF 9913 WX
LED temperature color	3000 K
Dimming	Optical sensor
Installation type	Surface Canopy
Materials	Profile: Aluminum Diffuser: Borosilicate
Light source	1 x LED STRIP 24V 17,2W G
LED	CRI>90 1504.8 lm 87.12 3000 K
Driver	Constant Voltage 100~240 V V 50~60 Hz HZ
Remarks	The glass is made of borosilicate. It is typical for the glass to have small air bubbles, some inclusions and tiny scratches. These do not affect the quality or the resistance of the glass. <div> <input type="checkbox"/> F Dimmer LED </div> <div> <input type="checkbox"/> IP20 <input type="checkbox"/> Bi-volt <input type="checkbox"/> Dry Location <input type="checkbox"/> 50-60Hz </div>
Application	Wall Lamps
Packaging	1 Box 1.12 m x 1.12 m x 0.345 m Gross weight 24.8 Net weight 11.5 Vol. 0.4327

Lighting effect

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency	1
Coordinate System	CG
Total Flux	897.91 lm
Maximum Value	188.65 cd/klm

Other Applications

