








Design By Ramos & Bassols

The Spa wall or ceiling lamp is suitable for damp areas. Its versatile system enables the luminaries to be placed in a line to illuminate four metres and a half of wall or ceiling space.

Model Sheet

Finish	 25 Beige D1 NCS S 4005-Y50R
	 11 Black NCS S 8500-N
	 23 Warm White NCS S 0502-Y50R
LED temperature color	2700 K / 3500 K
Dimming	Casambi / DALI / 1-10V
Installation type	Remote basic / Surface Canopy

Materials	Body: Aluminum Diffuser: PMMA Ceiling rose: Aluminum
Light source	2 x LED STRIP 21,6W 600mA 
LED	CRI>90 5120 lm 119 2700 K / 3500 K
Driver	Constant Current 1200 220~240 V V 50~60 Hz HZ

 Dimmable  50-60Hz  1-10V

Application	Ceiling Lamps
-------------	---------------

Packaging	1 Box 2.3 m x 0.1 m x 0.1 m Gross weight 4.2 Net weight 2.6 Vol. 0.023
-----------	--

Lighting effect

Linear

Linear lighting applications for functional and graphic illumination

Photometric Data

Go to vibia.com to get the photometric data for the different LED color temperatures.

Efficiency	60.77 lm/W
Coordinate System	CG
Total Flux	2143.97 lm
Maximum Value	915.55 cd

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com